

Hot Spot Public Access Point

Tabella Comparativa

RA-495

Main Technical Specification

- Radio Module Wi-Fi Standard
- IEEE802.11bg
- Bitrate 54Mbps
- 2 Antenne Sprinter removibili con Diversity (RP SMA)
- WAN Port: 1x10BASE-T/100BASE-TX RJ-45
- LAN Port: 4x10BASE-T/100BASE-TX RJ-45
- Plug and Play: Zero End-User Configuration
- Concurrent Users: Up to 100
- Rich Networking Functions

- NAT
- SMTP Server Redirect
- DNS
- Static IP WAN Connection
- DHCP Client WAN Connection
- PPPoE WAN Connection
- PPTP Client WAN Connection
- DHCP Server and DHCP Relay
- Transparent HTTP Proxy Support
- Bandwidth Control per user
- Session Control per user
- DDNS
- NTP Client

Management

- Web-based Management Tool
- TFTP/HTTP Firmware Upgrade
- Wizard setup for step-by-step Configuration
- Backup / Restore Configuration File
- Remote Authorized Management
- Real-time Session List
- LAN Device Management
- Syslog (System/Subscriber/LAN device)
- E-mail logs
- SNMP v1/v2 (MIB II, Private MIB)

User Accounting and Authentication

- Web-Based Authentication
- RADIUS AAA Support (RCF 2865,2866)
- Secondary RADIUS
- User Authentication and Accounting
- Logout Window Timer Control

Security

- SSL User Login page / Configuration Page
- Layer 2 Isolation Security
- Pass Through IP/MAC/URL Address
- VPN (IPSec/PPTP) Pass through
- PPTP VPN Client
- WEP
- WPA

Marketing Cooperation

- Standard Login Page
- Customizable log-on and log-off pages
- Advertisement URL Link
- Walled Garden
- WISPr Smart Client

Extra Functions with Thermal Printer

- Local Authentication, Accounting, Billing



Optional Ethernet Printer

	RA-495	RA-595	RTS-800
802.11b/g	✓	✓	-
Antenna Connector	RP SMA	RP SMA	-
Antenna	2 x RP SMA	2 x RP SMA	-
Ant. Diversity	✓	✓	-
WAN	1 Port	1 Port	2 Port
LAN	4 port	4 port	2 port
Plug & Play	✓	✓	✓
Users	Up to 100	Up to 50 concurrent, 500 local, 2.000 on-demand	Up to 500 conc., 2.500 local, 2.000 on-demand
NAT	RFC 1631	(1)IP/Port Dest. Redirect (2)DMZ (3)Virtual Server	(1)DMZ (2)Virtual Server (3)IP/Port Dest. Redirect (4)H.323 Pass-Through
Multiple Network	-	✓	✓
Controllable LAN Port Requiring Auth.	-	✓	✓
Config. Static Route	-	✓	✓
SMTP Server Redirection	✓	✓	-
Session Trace	✓	✓	✓
User Authentication and Accounting	On-demand, Radius	Local and On-demand, POP3(S), LDAP, RADIUS, NT Domain	Local and On-demand, POP3(S), LDAP, RADIUS, NT Domain
Authentication Mode	✓	✓	✓
Web-Based Auth.	✓	✓	✓
RADIUS AAA support	✓	✓	✓
Real-time Session List	✓	✓	✓
L2 Isolation	✓	✓	✓
Pass Through	IP, MAC, URL address	IP, MAC, URL address	IP, MAC, URL address
Ticket Printer	✓	✓	-
Printer with display	-	✓	-
Web-based config. tool	✓	✓	✓
Wizard setup	✓	✓	✓
SNMP Redirect Support	✓	✓	✓
Wall garden	✓	✓	✓
Power Requirement	External Power Adapter Output:5V,2A/PoE	External Power Adapter Output:12V,1,5A/PoE	Integrated Power 90-264VAC
Dimension	242(L)x130.5(W) x112.6(H)	243(L)x 150(W) x45.5(H)	426(L)x270(W) x44(H)
Weight	420 g	1,4 Kg	6 Kg
Mounting	Desktop, Wall mounted	Desktop, Wall mounted	19" 1U Rack Mount

Tutte le specifiche tecniche fornite sono da considerarsi indicative. Le specifiche tecniche del prodotto possono non corrispondere con le descrizioni sopra riportate. Esse possono variare senza preavviso. I pesi e le dimensioni sono approssimativi. Le immagini incluse in questo catalogo sono da considerarsi a scopo puramente illustrativo e possono non corrispondere con il prodotto reale. L' utilizzo di questi apparecchi non è consentito senza i permessi delle Autorità Governative ed il rispetto delle Normative dello Stato in cui si intende utilizzarli.



RayTalk Industries Srl

via Nicolino di Galasso, 19 Galazzano 47899
Serravalle Republic of San Marino (RSM)
country code +378
telephone 0549-901170 fax 0549-900890
info@raytalk.com - www.raytalk.com